



Dependable. Reliable. Professional.

# 527-20 WINDOW & DOOR FLASHING TAPE

**SPECIALTY TAPE**



- Backing:** Polyethylene
- Adhesive:** Butyl Rubber
- Liner:** White Polyethylene Film
- Specifications:** N/A
- Colors:** Black
- Available Size:** 6 in x 50 ft x 20 mil  
(152 mm x 15.2 m x 508 µm)

## Applications

- Flashing and sealing around window and door installations
- Sealing sidewall sheathing seams and deck-to-wall joints
- Sealing building envelope penetration areas against air and moisture infiltration
- Sealing corner board abutments

## Features

## Benefits

Butyl Rubber Adhesive	<ul style="list-style-type: none"> <li>• Provides a strong and immediate bond to most building surfaces</li> <li>• Compatible with silicone, butyl, polyurethane, and blended sealants or caulking materials</li> <li>• Excellent all-weather performance</li> </ul>
Polyethylene Backing	<ul style="list-style-type: none"> <li>• Tough and durable</li> <li>• Resists direct UV exposure for up to 1 year</li> </ul>
Low VOC Content	<ul style="list-style-type: none"> <li>• Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®</li> </ul>

## Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	20 mils	508 µm	ASTM D-1000
<b>Adhesion to Steel</b>	125 oz/in	13.68 N/cm	PSTC-101
<b>Tensile Strength</b>	28 lb/in	49.04 N/cm	ASTM D-1000
<b>Installation Temperature</b>	20 to 160 °F	-7 to 71 °C	
<b>Operating Temperature</b>	-20 to 180 °F	-29 to 82 °C	
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH			
Standard Shelf Life (at 25 °C): 36 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.